

SERIES 35

SCISSORS LIFTS

Series 35 is the most versatile and popular family of lifts. This family of lifts can be used in a wide variety of applications – such as pallet build-up and tear-down, part assembly and disassembly and conveyor systems – to improve worker ergonomics or enhance plant efficiencies. The Series 35 reduces worker fatigue and reduces the risk of back injuries. Series 35 offers a high quality, low cost lifting solution.

- SERIES 35
- SERIES 35 EXTRA WIDE
- SERIES 35 EXTRA NARROW
- SERIES 35 ROVER
- SERIES 35 DOUBLE LONG
- SERIES 35 DOUBLE HIGH
- SERIES 35 DOUBLE LONG

Autoquip
LIFTING SOLUTIONS
CORPORATION
www.autoquip.com

NEW
MODELS



S35 SCISSORS LIFTS

KEY FEATURES

- Lubricated-for-life composite bearings on all pivot points
- Solid steel legs with stiffener bars
- Turned, ground, polished and hard-chromed axle pins
- Double-wire braided hydraulic hoses
- Velocity fuses on cylinders
- Polyethylene reservoir
- Maintenance (safety) locks in base frame
- Factory tested to 110% of capacity
- Internally mounted power unit
- Pre-wired power unit with UL approved and labeled control components
- Built and designed in accordance with ANSI MH29.1

OPTIONS

- Pit mounting (requires 8 1/2" lowered height)
- Accordion Skirts
- Portability package

BENEFITS

- Maintenance free bearings, no greasing
- Minimal platform deflection
- Extended bearing life
- Extended hose life for added safety
- Controlled descent in case of severed hose – Safety first!
- Reservoir will not contain rust, weld slag or condensation common with metal tanks. Allows visual checking of oil level.
- Easy access to hydraulic/electrical components for servicing
- Ready to operate lift with zero plumbing and minimal wiring
- Backed by the best warranty in the industry

POWER SUPPLY The electric motor is internally mounted. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24 VAC control voltage. The 36S15 has 115 VAC controls.

SPECIFICATIONS: 1,500 to 8,000 lb. Capacities, Travel Up to 60"

Travel (in.)	Lifting Capacity (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Lowered Height (in.)	Raised Height (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)	Model No.
to 24"	2,500	24x36	48x60	2,500	2,500	6 1/2	30 1/2	8	1.5	1	500	24S25
	4,000	24x36	48x60	4,000	4,000	6 1/2	30 1/2	11	1.5	1	510	24S40
	6,000	24x36	48x60	4,500	4,500	6 1/2	30 1/2	16	1.5	2	530	24S60
	8,000	24x36	48x60	4,500	4,500	7	31	22	1.5	2	650	24S80 NEW!
to 36"	1,500	24x48	48x72	1,000	750	6 1/2	42 1/2	28	0.5	1	580	36S15
	2,500	24x48	48x72	2,500	2,500	6 1/2	42 1/2	12	1.5	1	610	36S25
	4,000	24x48	48x72	3,500	3,500	6 1/2	42 1/2	17	1.5	1	620	36S40
	6,000	24x48	48x72	3,500	3,500	6 1/2	42 1/2	25	1.5	2	650	36S60
	8,000	24x48	48x72	3,500	3,500	7	43	34	1.5	2	750	36S80 NEW!
to 48"	2,500	24x64	48x96	2,500	2,500	7	55	16	1.5	1	820	48S25
	4,000	24x64	48x96	3,500	3,500	7	55	22	1.5	1	830	48S40
	6,000	24x64	48x96	3,500	3,500	7	55	33	1.5	2	860	48S60
	8,000	24x64	48x96	3,500	3,500	7 1/2	55 1/2	44	1.5	2	960	48S80 NEW!
to 60"	2,500	32x87	60x120	2,500	2,500	8	68	22	1.5	1	1,750	60S25 NEW!
	4,000	32x87	60x120	3,500	3,500	8	68	44	1.5	2	1,800	60S40 NEW!
	6,000	32x87	60x120	3,500	3,500	8	68	44	1.5	2	1,850	60S60 NEW!

S35 ROVER - MOBILE SCISSORS LIFT

The versatile Series 35 is even more versatile when it becomes mobile. Now high capacity lifting can easily be moved to and shared among various workstations as required. Simply unlock the wheels and roll to any position required. 110 VAC battery charger included.



Series 35 Rover - Portable 12 VDC Scissors Lift Model Specifications:

Travel (in.)	Lifting Capacity (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Lowered Height (in.)	Raised Height (in.)	Raising or Lowering Time (sec.)	Battery Operated	No. of Cyl.	Shipping Weight (lbs.)	Model No.
36"	2,500	24x48	48x72	2,500	1,500	14	50	12*	Battery Operated	1	1,000	36SRV25 NEW!
	4,000	24x48	48x72	3,000	1,500	14	50	17*		1	1,050	36SRV40 NEW!
	6,000	24x48	48x72	3,500	1,500	14	50	25*		2	1,100	36SRV60 NEW!

*Varies depending on amp draw in battery.

S35 EXTRA NARROW, EXTRA WIDE

KEY FEATURES

- Lubricated-for-life composite bearings on all pivot points
- Solid steel legs with stiffener bars
- Turned, ground, polished and hard-chromed axle pins
- Double-wire braided hydraulic hoses
- Velocity fuses on cylinders
- Polyethylene reservoir
- Maintenance (safety) locks in base frame
- Factory tested to 110% of capacity
- Internally mounted power unit (Extra Wide only)
- Pre-wired power unit with UL approved and labeled control components
- Built and designed in accordance with ANSI MH29.1

BENEFITS

- Maintenance free bearings, no greasing
- Minimal platform deflection
- Extended bearing life
- Extended hose life for added safety
- Controlled descent in case of severed hose – Safety first!
- Reservoir will not contain rust, weld slag or condensation common with metal tanks. Allows visual checking of oil level.
- Easy access to hydraulic/electrical components for servicing
- Ready to operate lift with zero plumbing and minimal wiring
- Backed by the best warranty in the industry

OPTIONS

- Pit mounting (requires 8 1/2" lowered height)
- Accordion Skirts
- Portability package

POWER SUPPLY The electric motor is internally mounted on Extra Wide models and remote for Extra Narrow models. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24 VAC control voltage.

SPECIFICATIONS: Series 35 Extra Wide Platform Scissors Lift Model Specifications: Up to 84" x 120"

Travel (in.)	Lifting Capacity (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Lowered Height (in.)	Raised Height (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)	Model No.
to 24"	2,500	48x36	60x60	2,500	2,500	6 1/2	30 1/2	16	1.5	2	715	24S25EXW
	4,000	48x36	60x60	4,000	4,000	6 1/2	30 1/2	16	1.5	2	715	24S40EXW
	6,000	48x36	60x60	4,500	4,500	6 1/2	30 1/2	16	1.5	2	715	24S60EXW
	8,000	48x36	60x60	4,500	4,500	7	31	22	1.5	2	825	24S80EXW NEW!
to 36"	2,500	48x48	60x72	2,500	2,500	6 1/2	42 1/2	25	1.5	2	855	36S25EXW
	4,000	48x48	60x72	3,500	3,500	6 1/2	42 1/2	25	1.5	2	855	36S40EXW
	6,000	48x48	60x72	3,500	3,500	6 1/2	42 1/2	25	1.5	2	855	36S60EXW
	8,000	48x48	60x72	3,500	3,500	7	43	34	1.5	2	965	36S80EXW NEW!
to 48"	2,500	48x64	60x96	2,500	2,500	7	55	33	1.5	2	1,095	48S25EXW
	4,000	48x64	60x96	3,500	3,500	7	55	33	1.5	2	1,095	48S40EXW
	6,000	48x64	60x96	3,500	3,500	7	55	33	1.5	2	1,095	48S60EXW
	8,000	48x64	60x96	3,300	3,500	7 1/2	55 1/2	44	1.5	2	1,210	48S80EXW NEW!
to 60"	2,500	60x87	84x120	2,500	2,500	8	68	44	1.5	2	2,300	60S25EXW NEW!
	4,000	60x87	84x120	3,500	3,500	8	68	44	1.5	2	2,350	60S40EXW NEW!
	6,000	60x87	84x120	4,500	3,500	8	68	44	1.5	2	2,400	60S60EXW NEW!

SPECIFICATIONS: Series 35 Extra Narrow Platform Scissors Lift Model Specifications: Remote P.U.

Travel (in.)	Lifting Capacity (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Lowered Height (in.)	Raised Height (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)	Model No.
to 24"	2,500	16x36	24x60	2,500	2,500	6.5	30 1/2	8	1.5	1	450	24S25EXN
	4,000	16x36	24x60	4,000	4,000	6.5	30 1/2	11	1.5	1	450	24S40EXN
to 36"	2,500	16x48	24x72	2,500	2,500	6.5	42 1/2	12	1.5	1	560	36S25EXN
	4,000	16x48	24x72	3,500	3,500	6.5	42 1/2	17	1.5	1	570	36S40EXN
to 48"	2,500	16x64	24x96	2,500	2,500	7	55	16	1.5	1	770	48S25EXN
	4,000	16x64	25x96	3,500	3,500	7	55	22	1.5	1	780	48S40EXN
to 60"	2,500	24x87	32x120	2,500	2,500	8	68	22	1.5	1	1,600	60S25EXN NEW!
	4,000	24x87	32x120	3,500	3,500	8	68	44	1.5	2	1,650	60S40EXN NEW!
	6,000	24x87	32x120	4,500	3,500	8	68	44	1.5	2	1,700	60S60EXN NEW!

S35 DOUBLE LONG, DOUBLE HIGH, DOUBLE WIDE

KEY FEATURES

- Lubricated-for-life composite bearings on all pivot points
- Solid steel legs with stiffener bars
- Turned, ground, polished and hard-chromed axle pins
- Double-wire braided hydraulic hoses
- Velocity fuses on cylinders
- Polyethylene reservoir
- Maintenance (safety) locks in base frame
- Factory tested to 110% of capacity

- Internally mounted power unit
- Pre-wired power unit with UL approved and labeled control components
- Built and designed in accordance with ANSI MH29.1

OPTIONS

- Pit mounting (requires 8 1/2" lowered height for single-high models)
- Accordion skirts

BENEFITS

- Maintenance free bearings, no greasing
- Minimal platform deflection
- Extended bearing life
- Extended hose life for added safety
- Controlled descent in case of severed hose – Safety first!
- Reservoir will not contain rust, weld slag or condensation common with metal tanks. Allows visual checking of oil level.
- Easy access to hydraulic/electrical components for servicing

- Ready to operate lift with zero plumbing and minimal wiring
- Backed by the best warranty in the industry

POWER SUPPLY The electric motor is internally mounted unless otherwise noted. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24 VAC control voltage.

SPECIFICATIONS: Series 35 Double Long, Double High and Double Wide

Travel (in.)	Lifting Capacity (lbs.)	Standard Platform & Base Frame (Inches)	Maximum Allowable Platform Size (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Lowered Height (in.)	Raised Height (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)	Model No.
--------------	-------------------------	---	---------------------------------------	----------------------	-----------------------	----------------------	---------------------	---------------------------------	---------------------	-------------	------------------------	-----------

Series 35 Double Long Scissors Lift Model Specifications: Up to 48" x 162"

to 24"	4,000	24x74	48x98	2,500	4,000	6 1/2	30 1/2	16	1 1/2	1	1,100	24S25DL
	6,400	24x74	48x98	4,000	6,400	6 1/2	30 1/2	22	1 1/2	1	1,150	24S40DL
	9,600	24x74	48x98	4,500	7,200	6 1/2	30 1/2	32	1 1/2	2	1,200	24S60DL
	12,000	24x74	48x98	4,500	7,200	7 1/4	31 1/4	44	1 1/2	2	1,400	24S80DL NEW!
to 36"	4,000	24x98	48x122	2,500	4,000	6 1/2	42 1/2	24	1 1/2	1	1,300	36S25DL
	6,400	24x98	48x122	3,500	5,600	6 1/2	42 1/2	34	1 1/2	1	1,350	36S40DL
	9,600	24x98	48x122	3,500	5,600	6 1/2	42 1/2	25*	5	2	1,400	36S60DL
to 48"	12,000	24x98	48x122	3,500	5,600	7 1/4	43 1/4	35*	5	2	1,650	36S80DL NEW!
	4,000	24x130	48x162	2,500	4,000	7	55	32	1 1/2	1	1,700	48S25DL
	6,400	24x130	48x162	3,500	5,600	7	55	22*	5	1	1,750	48S40DL
	9,600	24x162	48x162	3,500	5,600	7	55	33*	5	2	1,800	48S60DL
12,000	24x130	48x162	3,500	5,600	7 3/4	55 3/4	45*	5	2	2,100	48S80DL NEW!	

Series 35 Double High Scissors Lift Model Specifications: Up to 96" Travel

to 48"	2,400	24x36	36x60	2,000	1,000	13	61	16	1 1/2	1	1,100	24S25DH
	3,400	24x36	36x60	3,400	1,600	13	61	22	1 1/2	1	1,150	24S40DH
	5,400	24x36	36x60	3,500	1,600	13	61	32	1 1/2	2	1,200	24S60DH
	7,000	24x36	36x60	3,500	1,800	14	62	44	1 1/2	2	1,275	24S80DH NEW!
to 72"***	1,900	24x48	36x72	1,900	1,000	13	85	24	1 1/2	1	1,300	36S25DH
	3,400	24x48	36x72	3,000	1,400	13	85	34	1 1/2	1	1,350	36S40DH
	5,400	24x48	36x72	3,000	1,400	13	85	25*	5	2	1,400	36S60DH
	7,000	24x48	36x72	3,000	1,400	14	86	35*	5	2	1,475	36S80DH NEW!
to 96"***	1,700	24x64	36x96	1,700	1,000	14	110	32	1 1/2	1	1,700	48S25DH
	3,200	24x64	36x96	2,500	1,400	14	110	22*	5	1	1,750	48S40DH
	5,200	24x64	36x96	3,000	1,400	14	110	33*	5	2	1,800	48S60DH
	7,000	24x64	36x96	3,000	1,400	15	111	45*	5	2	1,875	48S80DH NEW!

Series 35 Double Wide Scissors Lift Model Specifications: Up to 72" x 96"

to 24"	4,000	48x36	72x60	4,000	2,500	6 1/2	30 1/2	16	1 1/2	1	1,100	24S25DW
	6,400	48x36	72x60	6,400	4,000	6 1/2	30 1/2	22	1 1/2	1	1,150	24S40DW
	9,600	48x36	72x60	7,200	4,500	6 1/2	30 1/2	32	1 1/2	2	1,200	24S60DW
	12,000	48x36	72x60	7,200	4,500	7 1/4	31 1/4	44	1 1/2	2	1,400	24S80DW NEW!
to 36"	4,000	48x48	72x72	4,000	2,500	6 1/2	42 1/2	24	1 1/2	1	1,300	36S25DW
	6,400	48x48	72x72	5,600	3,500	6 1/2	42 1/2	34	1 1/2	1	1,350	36S40DW
	9,600	48x48	72x72	5,600	3,500	6 1/2	42 1/2	25*	5	2	1,400	36S60DW
	12,000	48x48	72x72	5,600	3,500	7 1/4	43 1/4	35*	5	2	1,650	36S80DW NEW!
to 48"	4,000	48x64	72x96	4,000	2,500	7	55	32	1 1/2	1	1,700	48S25DW
	6,400	48x64	72x96	5,600	3,500	7	55	22*	5	1	1,750	48S40DW
	9,600	48x64	72x96	5,600	3,500	7	55	33*	5	2	1,800	48S60DW
	12,000	48x64	72x96	5,600	3,500	7 3/4	55 3/4	45*	5	2	2,100	48S80DW NEW!

*Note: Remote 5 hp super torque power units are standard for extra oil volume. **72" and 96" travel models may require guide systems and gates and enclosures. Consult with the factory.