

# EVANS MODEL 0256

## PINCH ROLLER (SOLID TOP AND BOTTOM ROLLER)

PROVEN A PERFECT FIT  
AROUND THE WORLD, IN ALL  
SIZE OPERATIONS!



The Evans Machinery Inc. **Model 0256 Pinch Roller** is a key asset for laminating shops, both large and small. The top roller is easily adjustable to the thickness of the work being laminated. Simply insert the provided spacers 1/8, 1/4, 1/2, and 3/4. You can use any combination to acquire the desired thickness.

The 0256 is specifically designed to laminate using either contact adhesives or the fast bond PVA's. The Evans unique design of the pressure roller allows for uniformed and even bonding of



- BONDS AT 50 FEET PER MINUTE
- SAFETY GATES ON INFEED AND OUT-FEED SIDES
- FAST, ACCURATE THICKNESS ADJUSTMENT
- WORKS WITH CONTACT ADHESIVE OR PVA (WHITE GLUE).
- HEAVY DUTY CONSTRUCTION

the laminate to the substrate.

Compare the features and performance. You too will make the same choice professionals all over the world have been making for over 40 years. Evans Machinery is still the number one choice.

## TECHNICAL SPECIFICATIONS

Electrical	110 Volt	Maximum Width	62"
Drive Motor	1/2 HP	Air Requirement	100 PSI
Amps	8	Feed Rate	50' FPM
Working height	30 1/2"	Foot print	74" x 28"
Maximum Thickness	2"	Weight crated	800 LBS

BECAUSE OF CONTINUOUS IMPROVEMENTS EVANS MACHINERY, INC. RESERVES THE RIGHT TO MAKE CHANGES TO SPECIFICATIONS



### EVANS MACHINERY, INC.

5530 N. 51ST AVENUE, GLENDALE, ARIZONA 85301

[www.evansmachineryinc.com](http://www.evansmachineryinc.com)

PHONE 623-934-7294 FAX 623-934-7384